

RENEGADE

THOMAS  Pro-Series

Built for Contractors – Built to Last



T-100SP



T-100ST

HIGH-QUALITY COMPONENTS

By using high-quality fittings, gauges and other components, the Renegade® Pro-Series provides the ultimate integrity of a long, service-free life.

PERMANENTLY LUBRICATED DESIGN

Means Renegade® Pro-Series starts quickly, even in the coldest of weather.



ELECTRICALLY FRIENDLY

Low current draw won't blow standard 15 AMP house circuits and extension cords can be used whenever and wherever you need one.



PATENTED LIFE-GUARD™ DIRT DEFLECTOR keeps job site dust and grit out of the compressor.



	T-100SP	T-100ST
Air Displacement	6.0 CFM	6.0 CFM
Air Delivery	3.1 CFM @ 100 PSI Max pressure to 135 PSI	3.1 CFM @ 100 PSI Max pressure to 135 PSI
Pressure Switch	Starts compressor @ 110 PSI Stops compressor @135 PSI	Starts compressor @ 110 PSI Stops compressor @ 135 PSI
Motor	1 HP electric motor Capacitor start	1 HP electric motor Capacitor start
Tanks Capacity	3 gallons	4 gallons
Shipping Weight	57 lbs.	66 lbs.
Net Weight	52 lbs.	61 lbs.
Dimensions: Unit L x W x H (in.): Ctn.	15 x 15 x 24 18.4 x 18.4 x 25.4	18.87 x 14.63 x 16.38 22.0 x 16.5 x 17.3
Low Amp Draw	13.0	13.0
Recovery Time	18 seconds	22 seconds
Regulator & Gauge	Supplied	Supplied
RPM	1725	1725
Decibel Rating	75 dB	75 dB
Finish Guns	3-4	3-4
Framing Guns	1-2	1-2
Roofing Guns	1-2	1-2

Quality Compressors for the Professional Contractor.



1419 Illinois Ave. • Sheboygan, WI 53081
1-800-558-7721 • FAX 920-451-4325

RENEGADE

THOMAS  Pro-Series

Built for Contractors – Built to Last



T-200ST



T-200

HIGH-QUALITY COMPONENTS

By using high-quality fittings, gauges and other components, the Renegade® Pro-Series provides the ultimate integrity of a long, service-free life.

PERMANENTLY LUBRICATED DESIGN

Means Renegade® Pro-Series starts quickly, even in the coldest of weather.



ELECTRICALLY FRIENDLY

Low current draw won't blow standard 15 AMP house circuits and extension cords can be used whenever and wherever you need one.



PATENTED LIFE-GUARD™ DIRT DEFLECTOR keeps job site dust and grit out of the compressor.



	T-200ST	T-200
Air Displacement	8.0 CFM	8.0 CFM
Air Delivery	4.6 CFM @ 100 PSI Max pressure to 135 PSI	4.6 CFM @ 100 PSI Max pressure to 135 PSI
Pressure Switch	Starts compressor @ 110 PSI Stops compressor @ 135 PSI	Starts compressor @ 110 PSI Stops compressor @ 135 PSI
Motor	2 HP electric motor Capacitor start/run	2 HP electric motor Capacitor start/run
Tanks Capacity	4 gallons	7 gallons
Shipping Weight	72 lbs.	101 lbs.
Net Weight	66 lbs.	90 lbs.
Dimensions: Unit L x W x H (in.): Ctn.	19 x 14.6 x 16.3 22 x 16.5 x 17.3	42.1 x 18 x 22.2 45 x 19.5 x 28.5
Low Amp Draw	13.0	13.0
Recovery Time	12 seconds	20 seconds
Regulator & Gauge	Supplied	Supplied
RPM	1725	1725
Decibel Rating	75 dB	75 dB
Finish Guns	5-6	5-6
Framing Guns	3-4	3-4
Roofing Guns	3-4	3-4

Quality Compressors for the Professional Contractor.

